



RETREAD SPECIFICATIONS

Size	Pattern	BUFFED CROWN RADIUS		BUFFED CROWN WIDTH		Rim Width
		mm	in	mm	in	in
11R22.5	S605	510.0	20.079	222.6	8.764	8.25
11R24.5		535.0	21.063	222.7	8.768	8.25
295/75R22.5		493.0	19.409	221.3	8.713	9.00
285/75R24.5		510.5	20.098	223.3	8.791	8.25
11R22.5	S606	510.0	20.079	222.8	8.772	8.25
11R24.5		535.0	21.063	222.9	8.776	8.25
12R22.5		527.5	20.768	233.8	9.205	8.25
295/75R22.5		493.0	19.409	221.1	8.705	9.00
295/80R22.5		625.0	24.606	220.0	8.661	9.00
285/75R24.5		510.5	20.098	223.5	8.799	8.25
315/80R22.5		648.5	25.531	246.0	9.685	9.00
11R22.5	S622	513.0	20.197	205.8	8.102	8.25
11R24.5		534.5	21.043	222.4	8.756	8.25
255/70R22.5		575.0	22.638	205.0	8.071	7.50
295/75R22.5		492.5	19.390	221.5	8.720	9.00
285/75R24.5		510.0	20.079	223.0	8.780	8.25
215/75R17.5	S637	372.5	14.665	163.0	6.417	6.00
235/75R17.5		387.0	15.236	181.3	7.138	6.75
225/70R19.5		393.5	15.492	182.9	7.201	6.75
245/70R17.5		407.0	16.024	203.8	8.024	6.75
245/70R19.5		407.0	16.024	203.8	8.024	7.50
265/70R19.5		590.0	23.228	200.0	7.874	7.50
255/70R22.5		452.5	17.815	204.8	8.063	7.50
275/70R22.5		580.0	22.835	230.0	9.055	7.50
9R22.5		522.0	20.551	185.0	7.283	6.75
10R22.5		452.5	17.815	204.8	8.063	7.50
215/75R17.5		S737	487.0	19.173	156.0	6.142
225/70R19.5	393.5		15.492	183.3	7.217	6.75
245/70R19.5	407.0		16.024	204.4	8.047	7.50
315/80R22.5	654.5		25.768	246.0	9.685	9.00
12R22.5	527.5		20.768	243.1	9.571	9.00
11R22.5	S753	510.0	20.079	220.8	8.693	8.25
11R24.5		535.0	21.063	220.9	8.697	8.25
295/75R22.5		492.5	19.390	220.6	8.685	9.00
285/75R24.5		510.0	20.079	219.9	8.657	8.25
11R22.5	S758	512.0	20.157	221.7	8.728	8.25
11R24.5		537.0	21.142	221.8	8.732	8.25
11R22.5	S768	510.0	20.079	220.8	8.693	8.25
11R24.5		535.0	21.063	220.9	8.697	8.25
295/75R22.5		492.5	19.390	220.6	8.685	9.00
285/75R24.5		510.0	20.079	219.9	8.657	8.25
11R22.5	S815	510.0	20.079	220.5	8.681	8.25
11R24.5		535.4	21.079	220.5	8.681	8.25
11.00R20		640.0	25.197	225.0	8.858	8.00
12R22.5		654.9	25.787	230.0	9.055	9.00
275/70R22.5		592.5	22.933	230.0	9.055	9.00
315/80R22.5		650.0	25.591	230.0	9.055	9.00
11R22.5	S665	860.0	33.858	220.0	8.661	8.25
11R24.5		860.0	33.858	220.0	8.661	8.25
295/75R22.5		620.8	24.441	220.0	8.661	9.00
285/75R24.5		440.0	17.323	220.0	8.661	8.25
11R22.5	SW01	890.0	35.039	226.0	8.898	8.25
11R24.5		890.0	35.039	226.0	8.898	8.25
11R22.5	S917	630.0	24.083	216.0	8.504	8.25
12R22.5		750.0	29.528	246.0	9.685	9.00
11R24.5		630.0	24.803	216.0	8.504	8.25
12.00R24		732.0	28.819	240.0	9.449	8.50
385/65R22.5	S825	800.0	31.496	298.0	11.732	11.75
425/65R22.5		800.0	31.496	310.0	12.205	12.25
445/65R22.5		800.0	31.496	330.0	12.992	13.00
225/70R19.5	S740	370.0	14.567	180.0	7.087	6.75
245/70R19.5		370.0	14.567	195.0	7.677	7.50
9.00R20	S811	535.0	21.063	195.0	7.677	7.00
10.00R20		600.0	23.622	214.0	8.425	7.50
11.00R20		640.0	25.197	223.0	8.780	8.00
12.00R20		700.0	27.559	240.0	9.449	8.50
10.00R20	S911	600.0	23.622	210.0	8.268	7.50
11.00R20		640.0	25.197	223.0	8.780	8.00

Every effort has been made to verify the accuracy of the listed specifications. TBC Corporation and TBC Brands cannot be held responsible for any discrepancies, and as such, the information should be considered as approximate.