

RETREAD SPECIFICATIONS



Size	Pattern	Buffed Crown Radius		Buffed Crown Width		Rim Width	
		mm	in	mm	in		
11R22.5	S605	660.0	26.0	220.0	8.66	8.25	
11R24.5		660.0	26.0	220.0	8.66	8.25	
295/75R22.5		711.0	28.0	220.0	8.66	9.00	
285/75R24.5		711.0	28.0	220.0	8.66	8.25	
11R22.5	S606	660.0	26.0	220.0	8.66	8.25	
11R24.5		660.0	26.0	220.0	8.66	8.25	
12R22.5		610.0	24.0	230.0	9.06	8.25	
295/75R22.5		711.0	28.0	220.0	8.66	9.00	
295/80R22.5		660.0	26.0	220.0	8.66	9.00	
285/75R24.5		711.0	28.0	220.0	8.66	8.25	
315/80R22.5		762.0	30.0	240.0	9.45	9.00	
11R22.5	S622	660.0	26.0	210.0	8.27	8.25	
11R24.5		660.0	26.0	210.0	8.27	8.25	
255/70R22.5		711.0	28.0	200.0	7.87	7.50	
295/75R22.5		711.0	28.0	220.0	8.66	9.00	
285/75R24.5	711.0	28.0	210.0	8.27	8.25		
215/75R17.5	S637	559.0	22.0	160.0	6.30	6.00	
235/75R17.5		660.0	26.0	180.0	7.09	6.75	
225/70R19.5		711.0	28.0	180.0	7.09	6.75	
245/70R17.5		711.0	28.0	200.0	7.87	6.75	
245/70R19.5		711.0	28.0	200.0	7.87	7.50	
265/70R19.5		610.0	24.0	200.0	7.87	7.50	
255/70R22.5		711.0	28.0	200.0	7.87	7.50	
275/70R22.5		762.0	30.0	230.0	9.06	7.50	
9R22.5		610.0	24.0	185.0	7.28	6.75	
10R22.5		610.0	24.0	200.0	7.87	7.50	
215/75R17.5		S637SP	559.0	22.0	175.0	6.89	6.00
225/70R19.5			711.0	28.0	185.0	7.28	6.75
245/70R19.5	711.0		28.0	225.0	8.86	7.50	
215/75R17.5	S737	508.0	20.0	155.0	6.10	6.00	
225/70R19.5		813.0	32.0	180.0	7.09	6.75	
245/70R19.5		711.0	28.0	200.0	7.87	7.50	
315/80R22.5		762.0	30.0	240.0	9.45	9.00	
12R22.5		610.0	24.0	240.0	9.45	9.00	
215/75R17.5	S737SP	508.0	20.0	155.0	6.10	6.00	
225/70R19.5		813.0	32.0	180.0	7.09	6.75	
245/70R19.5		711.0	28.0	200.0	7.87	7.50	
10R22.5	S753	610.0	24.0	200.0	7.87	7.50	
11R22.5		660.0	26.0	220.0	8.66	8.25	
11R24.5		610.0	24.0	220.0	8.66	8.25	
255/70R22.5		711.0	28.0	200.0	7.87	7.50	
295/75R22.5		711.0	28.0	220.0	8.66	9.00	
285/75R24.5		711.0	28.0	220.0	8.66	8.25	
11R22.5	S758	660.0	26.0	220.0	8.66	8.25	
11R24.5		610.0	24.0	220.0	8.66	8.25	
11R22.5	S768	660.0	26.0	220.0	8.66	8.25	
11R24.5		660.0	26.0	220.0	8.66	8.25	
295/75R22.5		711.0	28.0	220.0	8.66	9.00	
285/75R24.5		711.0	28.0	220.0	8.66	8.25	

Size	Pattern	Buffed Crown Radius		Buffed Crown Width		Rim Width
		mm	in	mm	in	
11R22.5	S815	660.0	26.0	220.0	8.66	8.25
11R24.5		610.0	24.0	220.0	8.66	8.25
11.00R20		660.0	26.0	220.0	8.66	8.00
12R22.5		660.0	26.0	230.0	9.06	9.00
255/70R22.5		711.0	28.0	200.0	7.87	7.50
275/70R22.5		762.0	30.0	230.0	9.06	9.00
315/80R22.5		762.0	30.0	230.0	9.06	9.00
11R22.5	S817	660.0	26.0	225.0	8.86	8.25
11R24.5		610.0	24.0	225.0	8.86	8.25
255/70R22.5		711.0	28.0	200.0	7.87	7.50
275/70R22.5		762.0	30.0	230.0	9.06	9.00
315/80R22.5		762.0	30.0	245.0	9.61	9.00
11R22.5	S665	660.0	26.0	220.0	8.66	8.25
11R24.5		610.0	24.0	220.0	8.66	8.25
295/75R22.5		711.0	28.0	220.0	8.66	9.00
285/75R24.5		711.0	28.0	220.0	8.66	8.25
295/75R22.5	SW01	660.0	26.0	235.0	9.25	9.00
11R22.5		711.0	28.0	235.0	9.25	8.25
11R24.5		711.0	28.0	235.0	9.25	8.25
11R22.5	S917	660.0	26.0	220.0	8.66	8.25
12R22.5		660.0	26.0	240.0	9.45	9.00
11R24.5		660.0	26.0	220.0	8.66	8.25
12.00R24		711.0	28.0	240.0	9.45	8.50
385/65R22.5	S825	1067.0	42.0	310.0	12.20	11.75
425/65R22.5		1067.0	42.0	330.0	12.99	12.25
445/65R22.5		1067.0	42.0	350.0	13.78	13.00
225/70R19.5	S740	813.0	32.0	190.0	7.48	6.75
245/70R19.5		711.0	28.0	200.0	7.87	7.50
225/70R19.5	S759	813.0	32.0	195.0	7.68	6.75
245/70R19.5		711.0	28.0	205.0	8.07	7.50
9.00R20	S811	660.0	26.0	195.0	7.68	7.00
10.00R20		610.0	24.0	220.0	8.66	7.50
11.00R20		660.0	26.0	220.0	8.66	8.00
12.00R20		711.0	28.0	240.0	9.45	8.50
10.00R20	S911	610.0	24.0	210.0	8.27	7.50
11.00R20		660.0	26.0	230.0	9.06	8.00
315/80R22.5	S698	762.0	30.0	240.0	9.45	9.00
11R22.5	S668	660.0	26.0	220.0	8.66	8.25
11R24.5		660.0	26.0	220.0	8.66	8.25
255/70R22.5		711.0	28.0	210.0	8.27	7.50
295/75R22.5		711.0	28.0	220.0	8.66	9.00
445/50R22.5	S696	2489.0	98.0	400.0	15.75	14.00
445/50R22.5	S705	2489.0	98.0	400.0	15.75	14.00
11R22.5	S757	711.0	28.0	240.0	9.45	8.25
11R24.5		711.0	28.0	240.0	9.45	8.25
295/75R22.5		762.0	30.0	240.0	9.45	9.00

Every effort has been made to verify the accuracy of the listed specifications. TBC Corporation and TBC Brands cannot be held responsible for any discrepancies, and as such, the information should be considered as approximate. These specs are a recommendation only. Buffing equipment can vary and, as such, the specs below should be verified for each different style of buffer. Buff profile should be verified using pilot skives of 3/32" across buffed tread surface. Version: TBC 11.21