

TIRE SIZE	kPA		450	480	520	550	590	620	655	690	720	760	790	825	860	900					
	psi		65	70	75	80	85	90	95	100	105	110	115	120	125	130					
215/75R17.5	DUAL	lbs.		3305	3415	3525(E)	124	3640	3750	3860(F)	127	3970	4080	4190(G)	130	4300	4410	4540(H)	133		
	SINGLE	lbs.		3525	3640	3750(E)	126	3860	3970	4080(F)	129	4190	4300	4410(G)	132	4540	4675	4805(H)	135		
235/75R17.5	DUAL	lbs.		4190	4300	4410(E)	132	4510	4675	4805(F)	135	4940	5070	5205(G)	138	5355	5510	5675(H)	141		
	SINGLE	lbs.		4410	4510	4675(E)	134	4805	4940	5070(F)	137	5205	5355	5510(G)	140	5675	5840	6005(H)	143		
245/70R17.5	DUAL	lbs.		4190	4300	4410(E)	132	4510	4675	4805(F)	135	4940	5070	5205(G)	138	5355	5510	5675(H)	141		
	SINGLE	lbs.		4410	4510	4675(E)	134	4805	4940	5070(F)	137	5205	5355	5510(G)	140	5675	5840	6005(H)	143		
225/70R19.5	DUAL	lbs.	2600(D)	114	2720	2860	3000(E)	119	3115	3245	3415(F)	123	3490	3615	3750(G)	126	3855	3970(H)	128		
	SINGLE	lbs.	2755(D)	116	2895	3040	3195(E)	121	3315	3450	3640(F)	125	3715	3845	3970(G)	128	4100	4190(H)	130		
245/70R19.5	DUAL	lbs.	2910		3070	3220	3415		3515	3655	3860(F)	127	3940	4075	4300(G)	131	4345	4540(H)	133		
	SINGLE	lbs.	3085		3265	3425	3640		3740	3890	4080(F)	129	4190	4335	4540(G)	133	4620	4805(H)	135		
265/70R19.5	DUAL	lbs.	3195		3430	3600	3750		3930	4095	4300		4405	4415	4675(G)	134					
	SINGLE	lbs.	3415		3650	3830	3970		4180	4355	4540		4685	4850	5070(G)	137					
10R22.5	DUAL	lbs.		3860	4045	4230		4410(E)	132	4585		4760	4940(F)	136	5075		5210	5355(G)	139		
	SINGLE	lbs.		4080	4280	4480		4675(E)	134	4850		5025	5205(F)	138	5360		5515	5675(G)	141		
11R22.5	DUAL	lbs.		4380	4580	4760		4950	5205(F)	138	5415		5625	5840(G)	142	5895	5950	6005(H)	143		
	SINGLE	lbs.		4530	4770	4990		5220	5510(F)	140	5730		5950	6175(G)	144	6320	6465	6610(H)	146		
12R22.5	DUAL	lbs.		4780	4990	5190		5390	5675(F)	141	5785		5895	6005(G)	143	6265	6525	6780(H)	147		
	SINGLE	lbs.		4940	5200	5450		5690	6005(F)	143	6205		6405	6610(G)	146	6870	7130	7390(H)	150		
315/80R22.5	DUAL	lbs.			5345	5675		5840	6070	6395(G)	145	6545	6770	6940(H)	148	7210	7610(J)	151	7910	8270(L)	154
	SINGLE	lbs.			5875	6175		6415	6670	6940(G)	148	7190	7440	7610(H)	151	7920	8270(J)	154	8690	9090(L)	157
295/80R22.5	DUAL	lbs.			4860	5070		5305	5525	5840		5945	6150	6395		6550	6780(H)	147	6950	7160(J)	149
	SINGLE	lbs.			5340	5510		5830	6070	6395		6535	6760	6940		7200	7390(H)	150	7640	7830(J)	152
295/75R22.5	DUAL	lbs.		4095	4300	4540		4690	4885	5070(F)	137	5260	5440	5675(G)	141	5795	6005(H)	143			
	SINGLE	lbs.		4500	4725	4940		5155	5370	5510(F)	140	5780	5980	6175(G)	144	6370	6610(H)	146			
275/70R22.5	DUAL	lbs.				4805		4940	5070	5205		5355	5510	5675		5840	6005		6175	6395(H)	145
	SINGLE	lbs.				5205		5355	5510	5675		5840	6005	6175		6395	6610		6780	6940(H)	148
255/70R22.5	DUAL	lbs.	3415		3585	3765		3970	4110	4275		4410	4455	4610	4675(G)	134	4915	5070(H)	137		
	SINGLE	lbs.	3640		3815	4005		4190	4370	4550		4675	4895	5065	5205(G)	138	5400	5510(H)	140		
385/65R22.5	DUAL	lbs.																			
	SINGLE	lbs.	6060		6380	6720		6940	7350	7650		8050	8230	8510	8820	9050	9370(J)	158		9920(L)	160
425/65R22.5	DUAL	lbs.																			
	SINGLE	lbs.	7210		7590	7990		8270	8740	9100		9370	9790	10100	10500(J)	162	10700	11400(L)	165		
445/65R22.5	DUAL	lbs.																			
	SINGLE	lbs.	7800		8230	8660		9090	9480	9870		10200(H)	10600	11000	11400		11700	12300(L)	168		12800(M)
445/50R22.5	DUAL	lbs.																			
	SINGLE	lbs.	6175		6570	6940		7310	7680	8030		8390	8740	9090	9370(J)	158	9780	10200(L)	161		
12.00R24	DUAL	lbs.		6120	6390	6650		6910	7160	7390(G)	150	7610	7830	8050(H)	153	8300	8540(J)	155			
	SINGLE	lbs.		6330	6660	6980		7280	7580	8050(G)	153	8310	8570	8820(H)	156	9100	9370(J)	158			
11R24.5	DUAL	lbs.		4660	4870	5070		5260	5510(F)	140	5675		5840	6005(G)	143	6205	6405	6610(H)	146		
	SINGLE	lbs.		4820	5070	5310		5550	5840(F)	142	6095		6350	6610(G)	146	6790	6970	7160(H)	149		
285/75R24.5	DUAL	lbs.			4340	4540		4740	4930	5205(F)	138	5310	5495	5675(G)	141	5860	6175(H)	144			
	SINGLE	lbs.			4770	4940		5210	5450	5675(F)	141	5835	6040	6175(G)	144	6440	6780(H)	147			

\* Every effort has been made to verify the accuracy of the listed specifications. TBC Corporation and TBC Brands cannot be held responsible for any discrepancies, and as such, the information should be considered as approximate.

